

Features

- Current:5-300A, Voltage:100-1600V
- All models feature the same compact dimensions to provide a uniform mounting pitch
- Glass passivated diode chip
- Excellent power/volume ratio, High thermal conductivity
- Package, electrically insulated case

Typical Applications

- Eliminator supply, industrial automatic control
- Numerical-controlled machinery, telecontrol system

I _{F(AV)}	5-50A
V _{RRM}	100-1600V
V _F	1.1V
I _{FSM}	175A

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	VALUE		UNIT
			Min	Max	
I _{F(AV)}	Mean forward current	180 ° sine wave, 50Hz Double side cooled, THS=55°C	5	50	A
V _{RRM}	Repetitive peak reverse voltage	V _{DRM} &V _{RRM} tp=10ms V _{DSM} &V _{RSM} =V _{DRM} &V _{RRM} +100V	100	1600	V
V _{RMS}	RMS current		70	860	V
V _{DC}	DC blocking voltage		100	1600	V
I _{FSM}	Surge on-state current	sine wave		175	A
V _F	Diode forward voltage	I _F =17.5A		1.1	V
I _R	Reverse leakage current	T _a =25°C		10	uA
I _{R(H)}		T _a =100°C		200	uA
R _{th(j-c)}	Thermal impedance node to the shell	180 ° sine wave, single heat sink		5.0	°C/W
R _{th(c-a)}	Thermal impedance (shell to powder)	180 ° sine wave, single heat sink		8	°C/W
V _{iso}	Insulation voltage		2500		V
T _J	Stored temperature		-40	125	°C
T _{stq}	Stored temperature		-40	150	°C
W _t	Weight			47	g
Outline					

Outline:
Product picture:
